

Package: ciflyr (via r-universe)

June 8, 2026

Title Reachability-Based Primitives for Graphical Causal Inference

Version 0.1.2

Description Provides a framework for specifying and running flexible linear-time reachability-based algorithms for graphical causal inference. Rule tables are used to encode and customize the reachability algorithm to typical causal and probabilistic reasoning tasks such as finding d-connected nodes or more advanced applications. For more information, see Wienöbst, Weichwald and Henckel (2025) <[doi:10.48550/arXiv.2506.15758](https://doi.org/10.48550/arXiv.2506.15758)>.

License MIT + file LICENSE

URL <https://cifly.dev/>, <https://github.com/mwien/CIfly>

BugReports <https://github.com/mwien/CIfly/issues>

SystemRequirements Cargo (Rust's package manager), rustc

Depends R (>= 4.2)

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Config/rextendr/version 0.4.1

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Config/pak/sysreqs libclang-dev

Repository <https://mwien.r-universe.dev>

Date/Publication 2025-12-10 18:02:25 UTC

RemoteUrl <https://github.com/mwien/cifly>

RemoteRef HEAD

RemoteSha 5595232165463035debc9f449d0391db2ed01245

RemoteSubdir ciflyr

Contents

parseGraph	2
parseRuletable	3
parseSets	4
reach	5
Index	6

parseGraph	<i>Obtain an internal representation of a CIfly graph.</i>
------------	--

Description

Obtain an internal representation of a CIfly graph. Advanced usage only, mostly recommended for improving performance if the same graph is used multiple times. The parsed graph object can be passed to all methods with a graph argument. It is compatible with all ruletables that have the same EDGES ... line as the ruletable passed as argument.

Usage

```
parseGraph(graph, ruletable, tableAsString = FALSE)
```

Arguments

graph	A list mapping edge types to edge lists.
ruletable	Path to a ruletable file.
tableAsString	Optional argument to enable passing the ruletable as multi-line string. Default value is FALSE.

Value

Internal CIfly graph representation.

Examples

```
dsepTable <- "
  EDGES --> <--
  SETS X, Z
  START <-- AT X
  OUTPUT ...
  --> | <-- | current in Z
  ... | ... | current not in Z
"
edgelist <- list("-->" = rbind(c(1, 2), c(3, 2), c(2, 4)))

g <- parseGraph(edgelist, dsepTable, tableAsString=TRUE)
sets <- list("X" = c(1), "Z" = c(4))
reach(edgelist, sets, dsepTable, tableAsString=TRUE)
```

parseRuletable	<i>Obtain an internal representation of a Cifly ruletable.</i>
----------------	--

Description

Obtain an internal representation of a Cifly ruletable. Advanced usage only, mostly recommended for improving performance if the same ruletable is used multiple times. The parsed ruletable object can be passed to all methods with a ruletable argument.

Usage

```
parseRuletable(ruletable, tableAsString = FALSE)
```

Arguments

ruletable	Path to a ruletable file.
tableAsString	Optional argument to enable passing the ruletable as multi-line string. Default value is FALSE.

Value

Internal Cifly ruletable representation.

Examples

```
dsepTable <- "  
  EDGES --> <--  
  SETS X, Z  
  START <-- AT X  
  OUTPUT ...  
  --> | <-- | current in Z  
  ... | ... | current not in Z  
"  
  
rt <- parseRuletable(dsepTable, tableAsString=TRUE)  
edgelist <- list("-->" = rbind(c(1, 2), c(3, 2), c(2, 4)))  
sets <- list("X" = c(1), "Z" = c(4))  
reach(edgelist, sets, rt)
```

 parseSets

Obtain an internal representation of Cifly sets.

Description

Obtain an internal representation of Cifly sets. Advanced usage only, mostly recommended for improving performance if the same sets are used multiple times. The parsed sets object can be passed to all methods with a sets argument. It is compatible with all ruletables that have the same SETS ... line as the ruletable passed as argument.

Usage

```
parseSets(sets, ruletable, tableAsString = FALSE)
```

Arguments

sets	A list mapping set names to a list of elements.
ruletable	Path to a ruletable file.
tableAsString	Optional argument to enable passing the ruletable as multi-line string. Default value is FALSE.

Value

Internal Cifly sets representation.

Examples

```
dsepTable <- "
  EDGES --> <--
  SETS X, Z
  START <-- AT X
  OUTPUT ...
  --> | <-- | current in Z
  ... | ... | current not in Z
"
sets <- list("X" = c(1), "Z" = c(4))

s <- parseSets(sets, dsepTable, tableAsString=TRUE)
edgelist <- list("-->" = rbind(c(1, 2), c(3, 2), c(2, 4)))
reach(edgelist, s, dsepTable, tableAsString=TRUE)
```

reach	<i>Perform the CIfly algorithm specified in the passed ruletable.</i>
-------	---

Description

For the given graph and sets, a CIfly reachability algorithm is run according to the ruletable specified in the ruletable argument. The algorithm returns all reachable nodes. It is guaranteed to run in linear-time.

Usage

```
reach(graph, sets, ruletable, tableAsString = FALSE, verbose = FALSE)
```

Arguments

graph	A list mapping edge types to edge lists stored in matrix format.
sets	A list mapping set names to a list of elements.
ruletable	Path to a ruletable file.
tableAsString	Optional argument to enable passing the ruletable as multi-line string. Default value is FALSE.
verbose	Optional argument to enable logging. Default value is FALSE.

Value

A vector of all reachable nodes.

Examples

```
dsepTable <- "
  EDGES --> <--
  SETS X, Z
  START <-- AT X
  OUTPUT ...
  --> | <-- | current in Z
  ... | ... | current not in Z
"

edgelist <- list("-->" = rbind(c(1, 2), c(3, 2), c(2, 4)))
sets <- list("X" = c(1), "Z" = c(4))
reach(edgelist, sets, dsepTable, tableAsString=TRUE)
```

Index

parseGraph, [2](#)
parseRuleTable, [3](#)
parseSets, [4](#)
reach, [5](#)